

Listing of the Claims:

The listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1-11. (Canceled).

12. (Currently Amended) A method for triggering an occupant protection device in a vehicle, comprising:

detecting a first measured variable while simultaneously generating a corresponding first signal for indicating a necessity for triggering the occupant protection device;

detecting an acceleration value in a z direction while simultaneously generating a corresponding second signal, wherein the z direction is a vertical direction;

calculating a trigger signal for triggering the occupant protection device as a function of the first signal and the second signal; and

triggering the occupant protection device as a function of the calculated trigger signal.

13. (Previously Presented) The method as recited in Claim 12, wherein the first measure variable includes at least one of an acceleration value in an x direction, an acceleration value in a y direction, and a measured variable that describes at least one of an area ahead of the vehicle and a vehicle surroundings.

14. (Previously Presented) The method as recited in Claim 12, further comprising:

performing a first detecting of an acceleration value in at least one of an x direction and a y direction;

performing a second detecting of at least one of an area ahead of the vehicle and a vehicle surroundings;

simultaneously with at least one of the first detecting and the second detecting, simultaneously generating a third signal that is incorporated into the calculating of the trigger signal.

15. (Previously Presented) The method as recited in Claim 14, wherein:

the detecting of the first measured variable is performed by an acceleration sensor;
and

the detecting of at least one of the area ahead of the vehicle and the vehicle surroundings are accomplished by one of a radar sensor, a lidar sensor, a video sensor, and an ultrasonic sensor.

16. (Previously Presented) The method as recited in Claim 12, wherein:

the occupant protection device includes at least one of an airbag, an electrically operable side window, a sunroof, a seat, and one of a reversible seat belt tensioner and a pyrotechnical seat belt tensioners, and

the airbag includes at least one of a driver airbag, a passenger airbag, a side airbag, a head airbag, a knee airbag, and a window airbag.

17. (Previously Presented) The method as recited in Claim 12, further comprising:

reducing a level of the first signal in the calculating of the trigger signal as a function of at least one of the second signal and a vehicle model.

18. (Previously Presented) The method as recited in Claim 17, wherein one of:

only level peaks of the first signal are reduced as a function of the second signal, and
the level of the first signal is reduced by a predefined value as a function of a level of the second signal.

19. (Previously Presented) The method as recited in Claim 12, further comprising:

raising a trigger threshold for triggering the occupant protection device in the calculating of the trigger signal as a function of the second signal.

20. (Previously Presented) The method as recited in Claim 12, wherein one of a raising of a trigger threshold and a lowering of a level of the first signal is carried out in a calculating of the trigger signal as a function of one of a characteristic-velocity of the vehicle and a relative velocity of the vehicle with respect to an obstacle.

21. (Currently Amended) A device for triggering an occupant protection device in a vehicle, comprising:

a first detection device for detecting a first measured variable and for simultaneously generating a corresponding first signal for indicating a necessity for triggering the occupant protection device;

a second detection device for detecting an acceleration value in a z direction and for simultaneously generating a corresponding second signal, wherein the z direction is a vertical direction;

a calculation device for calculating a trigger signal for triggering at least one occupant protection device as a function of the first signal and the second signal; and

a trigger device for triggering the occupant protection device as a function of the calculated trigger signal.

22. (Previously Presented) The device as recited in Claim 21, further comprising:

a device for:

detecting a measured variable describing at least one of an area ahead of the vehicle and a vehicle surroundings, and

detecting at least one of an acceleration value in an x direction and an acceleration value in a y direction.